

## LINDY 3649X BLACK LINE DisplayPort 1.2 cables



56-4372 LINDY 36491 BLACK LINE DisplayPort 1.2 cable, 1m  
56-4373 LINDY 36492 BLACK LINE DisplayPort 1.2 cable, 2m  
56-4374 LINDY 36493 BLACK LINE DisplayPort 1.2 cable, 3m

A range of DisplayPort cables to suit entry level home and office applications requirements.

Black Line cables featuring triple shielded construction with 30AWG copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability with ABS connector housings.

UHD resolutions up to 4096 x 2160@60Hz 4:4:4 10bit supported. Black Line HDMI cables are also capable of transmitting 32 channel audio and Dolby True HD. Black Line DisplayPort cables are 4:4:4 colour spacing capable.

### Technical Specifications

Connector	Connector type	DisplayPort Male
	Housing material	ABS
	Connector plating	Nickel
	Pin construction	Phosphor Bronze
	Pin plating	24K Gold 3µm
	Connector dimensions	21 x 38.9 x 13.6mm
	Cable	Cable type
Jacket diameter		6mm
Jacket Colour		Black
Jacket Material		PVC
Conductor		30AWG Copper
Shielding		Copper braid 80%
Bandwidth		21.6Gbit/s
Maximum Resolution	4096 x 2160@60Hz 4:4:4 10bit	
Nominal Attenuation	300kHz – 825MHz	<5dB
	825MHz – 2.475GHz	<5dB
	2.475GHz – 4.125GHz	<12dB
	4.125MHz – 5.1GHz	<20dB
Min Bend Radius	48mm	
Operating Temperature	-20oC to 80oC	
Storage Temperature	-25 oC to 85 oC	
Compliances	RoHS, REACH, UL	